

Nuheat Cable Layout Assistant - 120V

THIS IS NOT A SPACING TOOL. The spacing between cable runs should be 3" throughout the entire installation. The distance shown in the tables below specifies the distance to install the cable off the walls.

Ensure that the Nuheat Cable is installed in areas where heating is essential (toe-kicks, immediately in front of toilet/shower/tub). DO NOT INSTALL the Nuheat Cable more than 1" from these areas. Adjustments need to be compensated in non-essential areas such as behind the toilet or behind the door.

This tool is a GENERAL GUIDELINE only.

Model No.	Sq Ft	Distance	Model No.	Sq Ft	Distance
N1C004008	4	2.2"	N1C050058	50	2.5"
	5	3.4"		51	2.9"
	6	4.4"		52	3.3"
	7	5.3"		53	3.7"
	8	6.0"		54	4.1"
N1C009012	9	2.2"	55	4.5"	
	10	3.1"	56	4.8"	
	11	3.9"	57	5.2"	
	12	4.6"	58	5.6"	
N1C013019	13	2.3"	N1C059073	59	2.4"
	14	3.1"		60	2.8"
	15	3.8"		61	3.2"
	16	4.5"		62	3.6"
	17	5.1"		63	3.9"
	18	5.7"		64	4.3"
N1C020022	19	6.0"		65	4.6"
	20	2.8"		66	5.0"
	21	3.4"		67	5.3"
	22	4.0"		68	5.6"
N1C023028	23	2.7"		69	5.9"
	24	3.3"		70	6.0"
	25	3.8"		71	6.0"
	26	4.4"		72	6.0"
	27	4.9"		73	6.0"
	28	5.4"	N1C074088	74	2.0"
N1C029036	29	2.7"		75	2.0"
	30	3.2"		76	2.0"
	31	3.7"		77	2.2"
	32	4.2"		78	2.5"
	33	4.7"		79	2.9"
	34	5.1"		80	3.2"
	35	5.6"		81	3.5"
N1C037045	36	6.0"		82	3.8"
	37	2.6"		83	4.1"
	38	3.0"		84	4.4"
	39	3.5"		85	4.7"
	40	3.9"		86	5.0"
	41	4.4"		87	5.3"
	42	4.8"		88	5.6"
	43	5.2"	N1C089100	91	3.0"
	44	5.6"		92	3.3"
	45	6.0"		93	3.6"
N1C046049	46	2.6"		94	3.9"
	47	3.1"		95	4.2"
	48	3.5"		96	4.5"
	49	3.9"		97	4.8"
		98		5.1"	
		99		5.4"	
		100		5.7"	

Nuheat Cable Layout Assistant - 240V

THIS IS NOT A SPACING TOOL. The spacing between cable runs should be 3" throughout the entire installation. The distance shown in the tables below specifies the distance to install the cable off the walls.

Ensure that the Nuheat Cable is installed in areas where heating is essential (toe-kicks, immediately in front of toilet/shower/tub). DO NOT INSTALL the Nuheat Cable more than 1" from these areas. Adjustments need to be compensated in non-essential areas such as behind the toilet or behind the door.

This tool is a GENERAL GUIDELINE only.

Model No.	Sq Ft	Distance	Model No.	Sq Ft	Distance	Model No.	Sq Ft	Distance
N2C009014	9	2.3"	N2C073081	73	2.6"	N2C135154	135	2.5"
	10	3.2"		74	2.9"		136	2.7"
	11	4.0"		75	3.3"		137	3.0"
	12	4.7"		76	3.6"		138	3.2"
	13	5.4"		77	3.9"		139	3.5"
	14	6.0"		78	4.2"		140	3.7"
N2C015022	15	2.0"		79	4.5"		141	4.0"
	16	2.0"		80	4.9"		142	4.2"
	17	2.0"		81	5.2"		143	4.4"
	18	2.3"	N2C082089	82	2.5"		144	4.7"
	19	3.0"		83	2.8"		145	4.9"
	20	3.6"		84	3.2"		146	5.1"
	21	4.2"		85	3.5"		147	5.4"
	22	4.8"		86	3.8"		148	5.6"
N2C023031	23	2.0"		87	4.1"		149	5.8"
	24	2.0"		88	4.4"		150	6.0"
	25	2.2"		89	4.7"		151	6.0"
	26	2.8"	N2C090098	90	2.5"		152	6.0"
	27	3.3"		91	2.8"		153	6.0"
	28	3.8"		92	3.1"	N2C155175	155	2.4"
	29	4.3"		93	3.4"		156	2.7"
	30	4.8"		94	3.7"		157	2.9"
	31	5.3"		95	4.0"		158	3.1"
N2C032037	32	2.6"		96	4.3"		159	3.4"
	33	3.1"		97	4.6"		160	3.6"
	34	3.6"		98	4.9"		161	3.8"
	35	4.0"	N2C099116	99	2.5"		162	4.0"
	36	4.5"		100	2.8"		163	4.3"
	37	4.9"		101	3.1"		164	4.5"
N2C038044	38	2.5"		102	3.4"		165	4.7"
	39	2.9"		103	3.7"		166	4.9"
	40	3.4"		104	4.0"		167	5.2"
	41	3.8"		105	4.2"		168	5.4"
	42	4.2"		106	4.5"		169	5.6"
	43	4.7"		107	4.8"		170	5.8"
	44	5.1"		108	5.1"		171	6.0"
N2C045050	45	2.6"		109	5.3"		172	6.0"
	46	3.0"		110	5.6"		173	6.0"
	47	3.5"		111	5.9"		174	6.0"
	48	3.9"		112	6.0"		175	6.0"
	49	4.3"		113	6.0"	N2C176200	176	2.2"
	50	4.6"		114	6.0"		177	2.4"
N2C051062	51	2.7"		115	6.0"		178	2.6"
	52	3.1"		116	6.0"		179	2.9"
	53	3.5"	N2C117134	117	2.3"		180	3.1"
	54	3.9"		118	2.5"		181	3.3"
	55	4.3"		119	2.8"		182	3.5"
	56	4.6"		120	3.1"		183	3.7"
	57	5.0"		121	3.3"		184	3.9"
	58	5.4"		122	3.6"		185	4.2"
	59	5.7"		123	3.9"		186	4.4"
	60	6.0"		124	4.1"		187	4.6"
	61	6.0"		125	4.4"		188	4.8"
	62	6.0"		126	4.6"		189	5.0"
N2C063072	63	2.5"		127	4.9"		190	5.2"
	64	2.9"		128	5.1"		191	5.4"
	65	3.3"		129	5.4"		192	5.6"
	66	3.6"		130	5.6"		193	5.8"
	67	4.0"		131	5.9"		194	6.0"
	68	4.3"		132	6.0"		195	6.0"
	69	4.6"		133	6.0"		196	6.0"
	70	5.0"		134	6.0"		197	6.0"
	71	5.3"					198	6.0"
	72	5.6"					199	6.0"
							200	6.0"